

RLC Self-Aligning Accessories

FEATURES

- Capacities: 0.25-10T
- · Hardened components at all load bearing surfaces
- Rocker pin load introduction
- Stainless steel construction
- Built-in horizontal movement control and lift-off protection
- Load cell (re)placement after installation of the mount

APPLICATIONS

- Process control
- · Batch weighing
- Silo/hopper weighing
- · Belt scale weighing

DESCRIPTION


The RLC self-aligning silo mount, combined with the RLC load cell family, provides weighing assemblies suitable for process control, batch weighing, silo/hoppers, and belt scale applications.







The RLC self-aligning foot assembly is an ideal solution for medium capacity platform scales and belt scale applications.

The RLC mount and foot are based on a rocker pin design, combining excellent load introduction to the transducer with an overall low profile. Hardened stainless steel components are used at all bearing surfaces. The fully stainless steel construction guarantees long term reliability, even in the harshest environments.







| CAPACITY | 0.5T, 1T | 2T, 3.5T, 5T | 10T |
|----------|----------|--------------|-----|
| Α | 150 | 160 | 210 |
| В | 100 | 110 | 120 |
| С | 75 | 100 | 110 |
| D | 120 | 120 | 175 |
| E | 70 | 70 | 85 |
| F | 15 | 20 | 20 |
| G | 20 | 20 | 30 |
| V | Ø13 | Ø16 | Ø18 |

Revere



RLC Self-Aligning Accessories

ACCESSORIES

Self-Aligning Mount

The stainless steel RLC mount tolerates controlled movement in all directions. The silo or hopper is held captive, eliminating the need, unless major load movement is anticipated, for additional check rods. The unique design allows the load cell to be placed or replaced after installation of the mount.



Non-Adjustable Foot

The non-adjustable, stainless steel foot carries the same specifications as the height adjustable version, while providing an even lower profile.



Height-Adjustable Foot

This stainless steel foot, which has 5 mm of height adjustment, provides excellent load introduction to the load cell. The foot allows flexibility in platform design without compromising overall system performance.



| ADDITIONAL INFORMATION | | | | | |
|--|----------------|----------------|-----------|--|--|
| MOUNT/FOOT | 0.25-1T | 2-5T | 10T | | |
| Self-aligning mount | | | | | |
| Height, mount assembly + RLC (mm) | 75 | 100 | 110 | | |
| Outline drawing | 899043-00 | 899045-00 | 499094-10 | | |
| Mount assembly guideline | AG 05/7-100/01 | AG 05/7-100/01 | - | | |
| Non-adjustable foot | | | | | |
| Height of non-adjustable foot + RLC (mm) | 50 | 85.2 | - | | |
| Outline drawing non-adjustable foot | 899041-00 | 899042-00 | - | | |
| Height-adjustable foot | | | | | |
| Height of adjustable foot + RLC (mm) | 60+5 | 92.6+5 | 120.2+5 | | |
| Outline drawing adjustable foot | 499083-00 | 499084-00 | 499093-00 | | |